

WAGNER Anti-Corrosive Oil HD SAE 30

High-alloyed mineral motor oil containing special anti-corrosive substances.

Applications

For long-term preservation of engines and units.

Specification

- API SJ / CI-4

Under extreme conditions of use, WAGNER Anti-Corrosive Oil HD SAE 30 is a fully compatible engine oil. It guarantees high corrosion protection with ideal storage conditions over several years.

Advantages

- natural high viscosity index
- very good shear stability
- high oxidation stability
- excellent viscosity-temperature behavior
- high safety reserves for boundary lubrication conditions
- prevents black mud formation
- suitable for catalytic converters

Technical Data WAGNER Anti-Corrosive Oil HD SAE 30

Property	Test method	Test result	Unit
Density (15 °C)	DIN 51 757	0.892	g/cm ³
Viscosity (@ 40 °C)	DIN EN ISO 3104	99.9	mm ² /s
Viscosity (@ 100 °C)	DIN EN ISO 3104	11.7	mm ² /s
Viscosity index (VI)	DIN ISO 2909	106	
Flash point COC	DIN ISO 2592	245	°C
Pour point	DIN ISO 3016	-30	°C
Seawater Immersion Test	DIN 51 358	0	Grade
Base number	DIN ISO 3771	10.9	mg KOH/g

Packaging

Available Container	Content	Item No.
Metal canister	1 l	390001
Metal canister with handle	5 l	390005
Plastic canister	20 l	390020
Tight head drum (steel sheet)	200 l	390200

The information of this datasheet is made to the best of our knowledge and advises only a technically certified user on possible applications. WAGNER Spezialschmierstoffe is not liable for any property damage incurred as a result of improper use, mishandling, and or any use outside the prescribed method of use, purpose, or application. Any and all warranty and or damage claims will be subject to investigation on the use, method of application, and intent of application of the used product.