

WAGNER Classic Engine Oil SAE 50 unalloyed

Unalloyed multi-grade motor oil made from special, carefully selected raffinates.

Applications

WAGNER Classic Engine Oil SAE 50 unalloyed can be used in:

- classic cars, motorcycle and utility vehicles without full-flow oil filter, because it does not contain any cleaning and dirt removal additives (DD-detergent-dispersing additives).
- motorcycle engines with multi-disc clutch in oil bath (wet clutch / oil bath clutch)

Specifications

- API SA

Advantages

- resistant to oxidation
- not foaming
- excellent viscosity - temperature behaviour
- perfect lubrication at low and high temperatures
- does not damage white metal, non-ferrous metal alloys and sealing materials of classic vehicles

Technical Data WAGNER Classic SAE 50 unalloyed

Property	Test method	Test result	Unit
Relative density (@ 15 °C)	DIN EN ISO 12185	0.870-0.910	g/cm ³
Kin. viscosity (@ 100°C)	ASTM D7279	17.0-18.4	mm ² /s
Neutralisation number	DIN ISO 6618	max. 0.15	mg KOH/g
Flash point COC	DIN ISO 2592	min. 200	°C
Pour point	ASTM D7346	max. -21	°C

Packaging

Available Container	Content	Item No.
Metal canister	1 l	450001
Metal canister with handle	5 l	450005
Plastic canister	20 l	450020
Tight head drum (steel sheet)	200 l	450200

The information of this datasheet is made to the best of our knowledge and advises only a technically certified user on possible applications. WAGNER Spezienschmierstoffe is not liable for any property damage incurred as a result of improper use, mishandling, and or any use outside the prescribed method of use, purpose, or application. Any and all warranty and or damage claims will be subject to investigation on the use, method of application, and intent of application of the used product.