WAGNER Classic Gear Oil SAE 250

Mildly alloyed high-pressure gear oil for gearboxes for which the manufacturer's instructions do not require hypoid or EP gear oil types.

Applications

Especially for older vehicles, machinery and equipment.

Recommendations

- API GL3

The active ingredients used are tailored so that the white metals used in vintage vehicles, non-ferrous alloys and sealing materials are not damaged. WAGNER Classic Gear Oil SAE 250 is therefore ideal for steering and manual transmissions, shaft drives and differential gears of historic vehicles.

Advantages

- high load-bearing capacity
- superior viscosity-temperature behavior
- good adhesion and pressure-resistant lubricating films
- no foaming
- good air-separation ability
- wear reduction
- excellent oxidation stability

Technical Data WAGNER Classic Gear Oil SAE 250

Property	Test method	Test result	Unit
Density 15 °C	DIN EN ISO 12185	0.897	g/cm^3
Kin. viscosity @ 40 °C	DIN 51562-1	663.2	mm^2/s
Kin. viscosity @ 100 °C	DIN 51562-1	40.0	mm^2/s
Visocsity index	DIN ISO 2909	97	
Flash point COC	DIN ISO 2592	240	°C
Pour point	DIN ISO 3016	-21	°C
FZG test A8, 3/90	DIN ISO 14635-1	SKS: 12	

Packaging

Available Container	Content	Item No.
Metal canister	1 l	525001
Metal canister with handle	5 l	525005
Plastic canister	20 l	525020
Tight head drum (steel sheet)	200 l	525200

The information of this datasheet is made to the best of our knowledge and advises only a technically certified user on possible applications. WAGNER Spezialschmierstoffe is not liable for any property damage incurred as a result of improper use, mishandling, and or any use outside the prescribed method of use, purpose, or application. Any and all warranty and or damage claims will be subject to investigation on the use, method of application, and intent of application of the used product.

Wagner Spezialschmierstoffe GmbH & Co. KG
Speckbrodi 8 - 86759 Wechingen, Germany
☎ +49 9085 96009-10 - 🖷+49 9085 96009-29
✉ support@wagner-german-oil.com