



## TECHNICAL DATA SHEET

# Divinol Zweitaktöl FF

Semisynthetic two stroke motor oil with integrated fuel stabilizer

### PRODUCT DESCRIPTION

Low fuming semisynthetic multipurpose two stroke motor oil of the newest generation with an integrated fuel stabilizer. This high-class motor oil contains purifying and corrosion inhibiting compounds and can be used for combined or separated lubrication of air- and water cooled two-stroke engines of all types. Mixing of fuel is guaranteed due to emulsifying agents.

The benefits of Divinol Zweitaktöl FF:

- + Avoids ageing of the fuel mixture
- + Unproblematic winter storage of two stroke machines
- + Enables an quick and easy start of the engine
- + Protects from corrosion
- + Keeps fuel system clean

### CHARACTERISTICS

Colour / DIN ISO 2049	clear, red
Density/15°C / DIN EN ISO 12185	0,860 g/cm <sup>3</sup>
Viscosity/40°C / ASTM D 7042	56 mm <sup>2</sup> /s
Viscosity/100°C / ASTM D 7042	9.5 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270	154
Flash point (Cleveland) / DIN ISO 2592	100 °C
Pour point / ASTM D 7346	-21 °C

26150

03/2020-26150-17

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

