



TECHNICAL DATA SHEET

Divinol Tube KS

High-quality release agent with excellent corrosion protection for tunnel construction, concrete pipe construction and for vertical formwork

PRODUCT DESCRIPTION

- + high-quality release agent
- + based on mineral oils
- + free of solvents
- + high corrosion protection

CHARACTERISTICS

Colour / DIN ISO 2049	brighter 3.0
Density/15°C / DIN EN ISO 12185	850 kg/m ³
Viscosity/20°C / ASTM D 7042	19 mm ² /s
Flash point (Cleveland) / DIN ISO 2592	> 130 °C
Pour point / ASTM D 7346	< -21 °C
Operating temperature range	5 °C - 60 °C
Giscode	BTM 20
Water hazardous class	1

APPROVAL

As part of a DGNB certification, **Divinol Tube KS** can be used for quality level 1 (according to the catalog of criteria ENV 1.2 - risks to the local environment).

27820

02/2024-27820-13

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Tube KS

High-quality release agent with excellent corrosion protection for tunnel construction, concrete pipe construction and for vertical formwork

APPLICATION

Divinol Tube KS has proved itself for tunnel works and is suitable for plastic and steel formwork. The product has an excellent corrosion protection and forms a protective film on the mould frame. This does not affect the concrete surface negatively. **Divinol Tube KS** can be used in used in formwork rental warehouse for the storage of formwork elements outdoors. Use on heated formworks is possible.

Divinol Tube KS should be used as supplied by spraying, brushing or rolling.

STORAGE

Protect from strong sunlight. Store opened containers closed. If stored properly, it will last for at least 3 years.

MISCELLANEOUS

Consumption:

Depending on the type of formwork (absorbent, non-absorbent) approx. 8-30 g/m².

Processing:

The formwork must be pre-cleaned and dry. **Divinol Tube KS** is sprayed evenly and thinly with a high-pressure sprayer at 4-6 bar. Avoid accumulation of release agents. Concrete can be poured immediately after spraying.

Delivery form:

Container 1000 l

Barrels 200 l

Canister 20 l

27820

02/2024-27820-13

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Tube KS

High-quality release agent with excellent corrosion protection for tunnel construction, concrete pipe construction and for vertical formwork

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

27820

02/2024-27820-13

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

3 / 3