



TECHNICAL DATA SHEET

Divinol Zentralhydraulikfluid S

Synthetic Central Hydraulic Fluid

PRODUCT DESCRIPTION

Divinol Zentralhydraulikfluid S is a fully synthetic oil that meets the highest requirements. This product offers a high thermal stability, optimum foaming properties and good aging resistance. In addition, the product has an excellent low-temperature behavior. Due to the special additives **Divinol Zentralhydraulikfluid S** offers a high amount of corrosion protection component as well as maximum wear protection.

CHARACTERISTICS

Appearance	green / blue
------------	--------------

Density/15°C / DIN EN ISO 12185	830 kg/m ³
---------------------------------	-----------------------

Viscosity/40°C / ASTM D 7042	25 mm ² /s
------------------------------	-----------------------

Viscosity/100°C / ASTM D 7042	6 mm ² /s
-------------------------------	----------------------

Viscosity index / ASTM D 2270	>=190
-------------------------------	-------

Flash point (Cleveland) / DIN ISO 2592	>= 210 °C
--	-----------

Pour point / ASTM D 7346	<= -69°C
--------------------------	----------

DIVINOL RECOMMENDATION

Audi P/N G002000 / VW TL 52146

Audi P/N G002012

Chrysler MS-1872

Chrysler MS-5931, P/N 04883077

Chrysler MS-9602, ATF+4

28360

01/2025-28360-13

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Zentralhydraulikfluid S

Synthetic Central Hydraulic Fluid

Chrysler MS-10838, P/N 05142893AA
Ford M2C195-A
Ford M2C204-A (extended temp range)
GM P/N 89021184
GM 9985010, P/N 1052884
GM 9985835, P/N 12345866 (cold climate)
Hyundai / Kia PSF-3
Hyundai / Kia PSF-4
DTFR 38B100; MB 236.3, P/N 000 989 88 03
DTFR 31B120; MB 345.0, P/N 001 989 24 03
MAN M 3289
Mitsubishi PS Fluid
Mitsubishi Diamond SP III
Nissan PSF-II
Pentosin CHF 7.1
Pentosin CHF 11S
Pentosin CHF 202
Saab P/N (45) 30 09 800
Saab P/N 30 32 380
Subaru P/N K0209A0080
Toyota PSF Type EH, P/N 008886-01
VW P/N G002000
VW P/N G002012
VW TL 521 46 (G00200 / G00400)
Volvo P/N 1161529

APPLICATION

Suitable for central hydraulic systems (convertible top, steering, stability and traction systems), hydrostatic drives, level control, hydropneumatic suspension as well as power steering and damping. **Divinol Zentralhydraulikfluid S** is also suitable for refilling. Please see manufacturer's instructions.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

28360

01/2025-28360-13

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.