



TECHNICAL DATA SHEET

Divinol Spezial 2000 HD 10W

HD Monograde oil SAE 10W

PRODUCT DESCRIPTION

Monograde motor oil for wide application area. Divinol Spezial 2000 HD 10W has high reserves against wear and sludge. The product offers optimal lubrication as well as a very high oxidation stability even under difficult conditions.

CHARACTERISTICS

SAE Grade	10W
Colour / DIN ISO 2049	3.5
Density/15°C / DIN EN ISO 12185	0,86 g/cm ³
Viscosity/40°C / ASTM D 7042	28.6 mm ² /s
Viscosity/100°C / ASTM D 7042	4.1 mm ² /s
Viscosity index / ASTM D 2270	123
Flash point (Cleveland) / DIN ISO 2592	>200 °C
Pour point / ASTM D 7346	-33 °C
TBN	10.5 mgKOH/g

SPECIFICATION

API SJ/CF

48450

12/2020-48450-9

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

TECHNICAL DATA SHEET

Divinol Spezial 2000 HD 10W

HD Monograde oil SAE 10W

DIVINOL RECOMMENDATION

ACEA E1; MB 227.0; MAN 270; Volvo VDS

APPLICATION

All purpose HD single grade engine oil for Otto and Diesel engines and stationary motors. Also suitable as hydraulic medium for machines, the mix of proven base oils with additives ensures effective wear and corrosion protection.

48450

12/2020-48450-9

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co. KG · Schloßstraße 20 · 73054 Eisingen/Fils · Germany · Postfach 13 65 · 73054 Eisingen/Fils
Phone: +49 7161 802-0 · Fax: +49 7161 802-290 · info@zeller-gmelin.de · Geschäftsführer: Dipl.-Ing. (FH) Siegfried Müller
Dipl.-Kfm. Walter Jerusalem · Dipl.-Ing. (FH) Thomas Alpers · Kommanditgesellschaft · Sitz Eisingen · Amtsgericht Ulm HRA 530107
Persönlich haftende Gesellschafterin Zeller+Gmelin Verwaltungs GmbH · Sitz Eisingen · Amtsgericht Ulm HRB 530641