



## TECHNICAL DATA SHEET

# Divinol Spezial 2000 HD 30

## HD Monograde oil SAE 30

### PRODUCT DESCRIPTION

Monograde motor oil for wide application area. Divinol Spezial 2000 HD 30 has high reserves against wear and sludge. The product offers optimal lubrication as well as a very high oxidation stability even under difficult conditions.

### CHARACTERISTICS

SAE Grade	30
Density/15°C / DIN EN ISO 12185	0,88 g/cm <sup>3</sup>
Viscosity/40°C / ASTM D 7042	75
Viscosity/100°C / ASTM D 7042	10.9 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270	113
Flash point (Cleveland) / DIN ISO 2592	> 210 °C
Pour point / ASTM D 7346	-30 °C

### SPECIFICATION

API SJ/CF

### DIVINOL RECOMMENDATION

ACEA E1/E2; MB 227.0/228.0; MAN 270; Volvo VDS

48470

04/2021-48470-12

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

TECHNICAL DATA SHEET

## **Divinol Spezial 2000 HD 30**

HD Monograde oil SAE 30

### **APPLICATION**

All purpose HD single grade engine oil for Otto and Diesel engines and stationary motors. Also suitable as hydraulic medium for machines, the mix of proven base oils with additives ensures effective wear and corrosion protection.

48470

04/2021-48470-12

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2

**EXPERTLY DONE.**

Zeller+Gmelin GmbH & Co. KG · Schloßstraße 20 · 73054 Eisingen/Fils · Germany · Postfach 13 65 · 73054 Eisingen/Fils  
Phone: +49 7161 802-0 · Fax: +49 7161 802-290 · info@zeller-gmelin.de · Geschäftsführer: Dipl.-Ing. (FH) Siegfried Müller  
Dipl.-Kfm. Walter Jerusalem · Dipl.-Ing. (FH) Thomas Alpers · Kommanditgesellschaft · Sitz Eisingen · Amtsgericht Ulm HRA 530107  
Persönlich haftende Gesellschafterin Zeller+Gmelin Verwaltungs GmbH · Sitz Eisingen · Amtsgericht Ulm HRB 530641