



TECHNICAL DATA SHEET

Divinol HLP ISO 22

High pressure hydraulic oil, mineral based according to the requirements of DIN 51 524 part 2, HLP - viscosity: 22 mm²/s/40°C

PRODUCT DESCRIPTION

- + high pressure hydraulic oil
- + on the basis of mineral oil
- + with anti-oxidation and anti-corrosion agents
- + with wear and friction reducing additives
- + fulfils the requirements to hydraulic oils according to DIN 51 524 part 2, HLP

CHARACTERISTICS

Colour / DIN ISO 2049 max. 2.0

Density/15°C / DIN EN ISO 12185 860 kg/m³

Viscosity/40°C / ASTM D 7042 22 mm²/s

Flash point (Cleveland) / DIN ISO 2592 > 190

Pour point / ASTM D 7346 ≤ -27 °C

SPECIFICATION

International Specifications: SEB 181 222, AFNOR NF-E 48603, ASLE 70-1, 70-2 and 70-3, David Brown S1.53.101, VDMA 24318, CETOP RP91H, Vickers I-286-S3, Denison Hydraulics HF-2, Vickers M-2950-S

APPLICATION

Divinol HLP ISO 22 is used for all kinds of hydraulic aggregates, for which the use of HLP-alloyed oils is prescribed.

48850

05/2022-48850-11

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.



TECHNICAL DATA SHEET

Divinol HLP ISO 22

High pressure hydraulic oil, mineral based according to the requirements of DIN 51 524 part 2, HLP - viscosity: 22 mm²/s/40°C

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

48850

05/2022-48850-11

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co. KG · Schloßstraße 20 · 73054 Eisingen/Fils · Germany · Postfach 13 65 · 73054 Eisingen/Fils
Phone: +49 7161 802-0 · Fax: +49 7161 802-290 · info@zeller-gmelin.de · Geschäftsführer: Dipl.-Ing. (FH) Siegfried Müller
Dipl.-Kfm. Walter Jerusalem · Dipl.-Ing. (FH) Thomas Alpers · Kommanditgesellschaft · Sitz Eisingen · Amtsgericht Ulm HRA 530107
Persönlich haftende Gesellschafterin Zeller+Gmelin Verwaltungs GmbH · Sitz Eisingen · Amtsgericht Ulm HRB 530641