

TECHNICAL DATA SHEET

Divinol Multimax Premium 10W-40

Commercial vehicle engine oil based on synthesis technology - quality level ACEA E6/E7/E9/E11

PRODUCT DESCRIPTION

Divinol Multimax Premium 10W-40 is a high performance engine oil for use over the complete year. Stringent operating conditions by significantly higher mechanical and thermal requirements with regards to turbo charging technique is todays request to an engine oil as Divinol Multimax Premium 10W-40. At high temperatures Divinol Multimax Premium 10W-40 ensures trouble free lubrication performance and thus a stable, non-tearing oil lubricating film. Low temperature conditions are also perfectly mastered through Divinol Multimax Premium 10W-40 as well as longer oil change intervals - Divinol Multimax Premium 10W-40 can be used for extended oil drain intervals. Divinol Multimax Premium 10W-40 is designed specifically for heavy-duty commercial vehicle diesel engines with exhaust-optimized aggregates (also aftertreatment systems). Thus Divinol Multimax Premium 10W-40 can be easily used for the new emission standards.

CHARACTERISTICS

SAE Grade	10W-40
Appearance	clear
Density/15°C / DIN EN ISO 12185	0,86 g/cm ³
Sulphat ash / DIN 51575	< 1
Viscosity/40°C / ASTM D 7042	90 mm²/s
Viscosity/100°C / ASTM D 7042	13.6 mm²/s
Viscosity index / ASTM D 2270	> 150
Flash point (Cleveland) / DIN ISO 2592	232 °C

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it

10/2023-49110-26

49110



TECHNICAL DATA SHEET

Divinol Multimax Premium 10W-40

Commercial vehicle engine oil based on synthesis technology - quality level ACEA E6/E7/E9/E11

Pour point / ASTM D 7346	< -36°C
TBN	10 mgKOH/g

SPECIFICATION

API CK-4; ACEA E11/E9/E8/E7/E6; JASO DH-2

MANUFACTURER APPROVAL

DTFR 15C110 (MB 228.51); Deutz DQC IV-18 LA; Volvo VDS-4.5; Renault RLD-3; Mack EOS-4.5

Meet Caterpillar ECF-3 specification; Meet MAN 3477 specification

DIVINOL RECOMMENDATION

MAN 3775; DTFR 15C100 (MB 228.31); Scania LA; MTU 3.1; Cummins CES 20086; Detroit Diesel DDC 93K222; CNH MAT 3571; CNH MAT 3521/3522; Ford WSS-W2C171-E

APPLICATION

Divinol Multimax Premium 10W-40 is for heavy-duty diesel truck engines, including turbocharged and aftertreatment systems for the latest emission standards and longer oil change intervals in accordance with the recommended manufacturer's instructions.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49110 10/2023-49110-26

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it