



TECHNICAL DATA SHEET

Divinol Syntholight ASN 5W-30

High performance engine oil for API SP & ILSAC GF-6

PRODUCT DESCRIPTION

Divinol Syntholight ASN 5W-30 is a high performance engine oil especially for the lubrication of modern gasoline and ethanol engines (up to E85) in passenger cars, vans and SUVs. Through the effective, quality additive components **Divinol Syntholight ASN 5W-30** provides a top lubrication of all major components and thus a longer engine life for modern engines. **Divinol Syntholight ASN 5W-30** provides improved protection for the latest emission control systems and turbochargers. **Divinol Syntholight ASN 5W-30** is a hybrid-ready engine oil (H.E.V / P.E.H.V) and can also be used in vehicles with an **automatic start-stop system**. This motor oil covers ILSAC GF-6A and API SP.

Advantages of **Divinol Syntholight ASN 5W-30**:

- + low wear during cold starts / low temperatures
- + low oil consumption, hardly no evaporation loss
- + protect your exhaust aftertreatment systems

CHARACTERISTICS

SAE Grade	5W-30
Density/15°C / DIN EN ISO 12185	0,85 g/cm ³
Viscosity/40°C / ASTM D 7042	62 mm ² /s
Viscosity/100°C / ASTM D 7042	11.5 mm ² /s
Viscosity index / ASTM D 2270	177
Flash point (Cleveland) / DIN ISO 2592	210 °C

49150

10/2023-49150-17

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Syntholight ASN 5W-30

High performance engine oil for API SP & ILSAC GF-6

Pour point / ASTM D 7346 - 39 °C

TBN 8 mgKOH/g

SPECIFICATION

API SP/SN Plus; ILSAC GF-6A

DIVINOL RECOMMENDATION

DEXOS 1 Gen.3; Chrysler MS-6395; GM 6094M; Ford WSS-M2C961-A1; Ford WSS-M2C946-B1

APPLICATION

Divinol Syntholight ASN 5W-30 is designed for spark ignition with or without turbo charger and E-Hybrid vehicles.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49150

10/2023-49150-17

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

2 / 2