

TECHNICAL DATA SHEET

Divinol Syntholight DPF 5W-30

Premium Longlife III oil

PRODUCT DESCRIPTION

Divinol Syntholight DPF 5W-30 is the perfect product to reduce variety of motor oils. In almost all modern automobile types of BMW, Mercedes, VW, Audi and other manufacturers this oil can be filled. It doesn't matter if the vehicle is equipped with or without a diesel particulate filter or catalyser. This motor oil guarantees a maximal lifespan of exhaust aftertreatment in diesel and gas engines due to use of special additives. Also suitable for VW R5 and V10 TDI motors from year 01/2007. **Divinol Syntholight DPF 5W-30** is a **hybrid-ready engine oil (H.E.V / P.E.H.V)** and can also be used in vehicles with an **automatic start-stop system**.

Divinol Syntholight DPF 5W-30 has following advantages:

- + a low ash content, which leads to a reduction in the build-up of particles in diesel particulate filters
- + low sulfur and phosphorus content
- + excellent low temperature properties
- + fuel saving charcterisics
- + low oil consumption
- + universal usability in a wide variety of modern cars

CHARACTERISTICS

Colour / DIN ISO 2049	L 4.0
SAE Grade	5W-30
Appearance	slightly brown, clear
Density/15°C / DIN EN ISO 12185	0,850 g/cm³
Ash / Sulfate DIN 51575	0.5 %

49180 05/2024-49180-24

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it



TECHNICAL DATA SHEET

Divinol Syntholight DPF 5W-30

Premium Longlife III oil

Viscosity/40°C / ASTM D 7042	69.8 mm²/s
Viscosity/100°C / ASTM D 7042	12.1 mm²/s
Viscosity index / ASTM D 2270	170
Flash point (Cleveland) / DIN ISO 2592	235 °C
Pour point / ASTM D 7346	-42 °C
TBN	6.6 mgKOH/g

SPECIFICATION

ACEA C3; API SN

MANUFACTURER APPROVAL

MB-Approval 229.51; VW 504.00/507.00 (Longlife-III); BMW Longlife-04

DIVINOL RECOMMENDATION

Porsche C 30

APPLICATION

Divinol Syntholight DPF 5W-30 is compatible with exhaust aftertreatment systems and catalytic converters. Due to the performance **Divinol Syntholight DPF 5W-30** is universally suitable for a lot of passenger cars, in particular of the brands Mercedes, BMW, VW, Audi and others - also with extended oil change intervals - as well as for E-hybrid vehicles. Also suitable for LPG / CNG powered engines. Note manufacturer's instructions!

49180 05/2024-49180-24

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it



TECHNICAL DATA SHEET

Divinol Syntholight DPF 5W-30

Premium Longlife III oil

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49180 05/2024-49180-24

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.