



TECHNICAL DATA SHEET

Divinol Syntholight 03 5W-30

High quality motor oil SAE 5W30 according ACEA C3

PRODUCT DESCRIPTION

High-performance engine oil on the basis of advanced technology known as third longlife generation of motor oil. Many passenger cars and light duty vehicles built by VW Group and other vehicle manufacturers can be filled with this engine oil. **Divinol Syntholight 03 5W-30** offers optimal lubricating safety over the entire maintenance interval period and is suitable for exhaust gas aftertreatment systems such as diesel particulate filters. The slightly lowered HTHS viscosity enables fuel savings and thus also contributes to protect the environment. **Divinol Syntholight 03 5W-30** can be used in vehicles with an automatic start-stop system.

CHARACTERISTICS

SAE Grade	5W-30
Density/15°C / DIN EN ISO 12185	0,85 g/cm ³
Viscosity/40°C / ASTM D 7042	63 mm ² /s
Viscosity/100°C / ASTM D 7042	11 mm ² /s
Viscosity index / ASTM D 2270	167
Flash point (Cleveland) / DIN ISO 2592	210°C
Pour point / ASTM D 7346	<= -33°C
TBN	>= 6 mgKOH/g

SPECIFICATION

49251

05/2024-49251-33

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Syntholight 03 5W-30

High quality motor oil SAE 5W30 according ACEA C3

API SN; ACEA C3

DIVINOL RECOMMENDATION

VW 504.00/507.00; MB 229.51; BMW Longlife-04 (<2019); GM OPEL DEXOS 2; Porsche C30; PSA B71 2290 (>2017); PSA B71 2297

APPLICATION

Divinol Syntholight 03 5W-30 is ideal for portfolio reduction. Except for VW R5 and V10 engines produced before 2007.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49251

05/2024-49251-33

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

2 / 2