



TECHNICAL DATA SHEET

Divinol Syntholight HC-FE Plus 5W-30

Top modern 5W30 for broad use

PRODUCT DESCRIPTION

Divinol Syntholight HC-FE Plus 5W-30 is a completely new formulated motor oil for latest engine generation e. g. for BMW Longlife-04 (>2019). A smooth-running engine oil made by use of the most advanced HC synthesis technology. It is based on additives with low ash content (low-saps) for application in the most modern spark-ignition and diesel engines equipped with exhaust filter technology. Due to the HC synthesis technology, **Divinol Syntholight HC-FE Plus 5W-30** has a significantly lower evaporation propensity which has a positive effect on oil consumption. The viscosity class 5W-30 guarantees a rapid lubrication of the engine at low temperatures and a sufficiently thick lubricating film at high temperatures of up to 160 C°. **Divinol Syntholight HC-FE Plus 5W-30** is a hybrid-ready engine oil (H.E.V / P.E.H.V) and can also be used in vehicles with an **automatic start-stop system**. **Divinol Syntholight HC-FE Plus 5W-30** also works perfectly when biodiesel (~30%) is mixed in the fuel.

CHARACTERISTICS

Appearance brown, clear

Density/15°C / DIN EN ISO 12185 0,850 kg/m³

Viscosity/40°C / DIN 51 562 65.7 mm²/s

Viscosity/100°C / ASTM D 7042 12.2 mm²/s

Viscosity index / ASTM D 2270 180

SPECIFICATION

API SN/CF; ACEA C3

49280

03/2022-49280-7

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.



TECHNICAL DATA SHEET

Divinol Syntholight HC-FE Plus 5W-30

Top modern 5W30 for broad use

MANUFACTURER APPROVAL

MB-Approval 229.51

DIVINOL RECOMMENDATION

BMW Longlife-04; MB 229.52; MB 229.31; MB 226.52; GM OPEL DEXOS 2; Renault RN 0700/0710; Renault RN 17

APPLICATION

Divinol Syntholight HC-FE Plus 5W-30 meets the high performance and quality level for modern gasoline, diesel engines and E-Hybrid vehicles. This oil guarantees an extremely long-lasting efficiency of subsequent exhaust aftertreatment systems.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49280

03/2022-49280-7

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2

EXPERTLY DONE.

Zeller+Gmelin GmbH & Co. KG · Schloßstraße 20 · 73054 Eisingen/Fils · Germany · Postfach 13 65 · 73054 Eisingen/Fils
Phone: +49 7161 802-0 · Fax: +49 7161 802-290 · info@zeller-gmelin.de · Geschäftsführer: Dipl.-Ing. (FH) Siegfried Müller
Dipl.-Kfm. Walter Jerusalem · Dipl.-Ing. (FH) Thomas Alpers · Kommanditgesellschaft · Sitz Eisingen · Amtsgericht Ulm HRA 530107
Persönlich haftende Gesellschafterin Zeller+Gmelin Verwaltungs GmbH · Sitz Eisingen · Amtsgericht Ulm HRB 530641