



TECHNICAL DATA SHEET

Divinol Syntholight Eco 5W-20

Modern engine oil for Ford Eco-Boost engines

PRODUCT DESCRIPTION

Modern engine oil based on special base oils and additive components for use in Ford ECO BOOST engines. **Divinol Syntholight Eco 5W-20** can be called particularly fuel-efficient and emission reducing. Of course, the product also provides a fast lubrication of the engine and thus significantly reduces wear in the cold-starting period of the motor. **Divinol Syntholight Eco 5W-20** offers an optimum oil supply and therefore lubrication reliability in terms of the oil film. **Divinol Syntholight Eco 5W-20** is a hybrid-ready engine oil (H.E.V / P.E.H.V) and can also be used in vehicles with an **automatic start-stop system**.

Advantages:

- + saves fuel
- + unique dispersion properties ensure excellent engine cleanliness
- + excellent cleaning properties of all engine components
- + corrosion protection
- + excellent anti-wear properties
- + outstanding reliability of the lubricating film
- + very high aging stability

CHARACTERISTICS

Colour / DIN ISO 2049	≤ 3.5
SAE Grade	5W-20
Appearance	slightly brown, clear
Density/15°C / DIN EN ISO 12185	0,850 g/cm ³
Viscosity/40°C / ASTM D 7042	47 mm ² /s

49380

03/2022-49380-13

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.



TECHNICAL DATA SHEET

Divinol Syntholight Eco 5W-20

Modern engine oil for Ford Eco-Boost engines

Viscosity/100°C / ASTM D 7042	8.1 mm ² /s
-------------------------------	------------------------

Viscosity index / ASTM D 2270	≤ 155
-------------------------------	-------

Flash point (Cleveland) / DIN ISO 2592	210 °C
--	--------

Pour point / ASTM D 7346	-42 °C
--------------------------	--------

TBN	7.5 mgKOH/g
-----	-------------

SPECIFICATION

API SN; ACEA C5

DIVINOL RECOMMENDATION

Ford WSS-M2C 948-B; Jaguar LandRover STJLR.03.5004

APPLICATION

Divinol Syntholight Eco 5W-20 is recommended for Otto / gasoline engines or E-Hybrid vehicles with or without exhaust after treatment systems considering the manufacturers instructions in each case.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49380

03/2022-49380-13

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2