



## TECHNICAL DATA SHEET

# Divinol Syntholight 10W-60

High performance oil for powerful engines

### PRODUCT DESCRIPTION

**Divinol Syntholight 10W-60** is a premium engine oil which is especially developed for use in engines under extreme thermal stress. The combination of synthetic & hc synthetic base oils with a high-grade additives ensures an outstanding engine oil also for use in motor sports. Divinol Syntholight 10W-60 can be used in petrol and diesel engines with or without turbochargers and is ideally suited for racing use.

Also suitable for use in motorcycles with the specification **JASO MA-2**.

#### Advantages:

- + unique dispersing properties ensure excellent engine cleanliness
- + outstanding cleaning properties of all engine components
- + corrosion treatment
- + excellent anti-wear and
- + outstanding lubricant reliability
- + very high aging stability

### CHARACTERISTICS

Colour / DIN ISO 2049	5
SAE Grade	10W-60
Density/15°C / DIN EN ISO 12185	0,850 g/cm <sup>3</sup>
Ash / Sulfate DIN 51575	0.9 %
Viscosity/40°C / ASTM D 7042	164 mm <sup>2</sup> /s
Viscosity/100°C / ASTM D 7042	23 mm <sup>2</sup> /s

49390

05/2022-49390-11

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.



## TECHNICAL DATA SHEET

# Divinol Syntholight 10W-60

High performance oil for powerful engines

---

Viscosity index / ASTM D 2270	≥ 165
-------------------------------	-------

---

Flash point (Cleveland) / DIN ISO 2592	≥ 220 °C
--	----------

---

Pour point / ASTM D 7346	-39 °C
--------------------------	--------

---

TBN	8.2 mgKOH/g
-----	-------------

---

### SPECIFICATION

API SL/CF; JASO MA-2

### APPLICATION

Synthetic & HC synthetic blended high-tech engine oil for all Otto and Diesel engines including turbo-supercharger. Divinol Syntholight 10W-60 is suitable for passenger cars, muscle cars, motorcycles and older vehicles.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49390

05/2022-49390-11

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2