



## TECHNICAL DATA SHEET

# Divinol Spezial 2000 HD 50

## HD Monograde oil SAE 50

### PRODUCT DESCRIPTION

Monograde motor oil for wide application area. Divinol Spezial 2000 HD 50 has high reserves against wear and sludge. The product offers optimal lubrication as well as a very high oxidation stability even under difficult conditions.

### CHARACTERISTICS

SAE Grade	50
Density/15°C / DIN EN ISO 12185	0,88 g/cm <sup>3</sup>
Pour point / ASTM D 7346	-24 °C
Viscosity/100°C / ASTM D 7042	17 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270	142
Flash point (Cleveland) / DIN ISO 2592	230 °C
TBN	11 mgKOH/g

### SPECIFICATION

API SJ/CF/CF-2

### DIVINOL RECOMMENDATION

ACEA E1/E2; MB 227.0/228.0; MAN 270; MTU Type 1; Cat TO-2

49453

04/2021-49453-11

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

TECHNICAL DATA SHEET

## **Divinol Spezial 2000 HD 50**

HD Monograde oil SAE 50

### **APPLICATION**

Monograde motor oil for wide application area. Divinol Spezial 2000 HD 50 has high reserves against wear and sludge. The product offers optimal lubrication as well as a very high oxidation stability even under difficult conditions.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49453

04/2021-49453-11

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2

**EXPERTLY DONE.**

Zeller+Gmelin GmbH & Co. KG · Schloßstraße 20 · 73054 Eisingen/Fils · Germany · Postfach 13 65 · 73054 Eisingen/Fils  
Phone: +49 7161 802-0 · Fax: +49 7161 802-290 · info@zeller-gmelin.de · Geschäftsführer: Dipl.-Ing. (FH) Siegfried Müller  
Dipl.-Kfm. Walter Jerusalem · Dipl.-Ing. (FH) Thomas Alpers · Kommanditgesellschaft · Sitz Eisingen · Amtsgericht Ulm HRA 530107  
Persönlich haftende Gesellschafterin Zeller+Gmelin Verwaltungs GmbH · Sitz Eisingen · Amtsgericht Ulm HRB 530641