



## TECHNICAL DATA SHEET

# Divinol Syntholight WV 0W-20

Synthetic motoroil 0W-20 with VW 508.00/509.00

### PRODUCT DESCRIPTION

**Divinol Syntholight WV 0W-20** is a high-performance engine oil formulated on PAO base oils for the latest VW group engines (VW, Audi, Skoda, Seat) and Porsche. This lubricant supports an efficiency increase of the emission system, as well as fuel savings. In addition **Divinol Syntholight WV 0W-20** supports superior motor cleanliness, wear protection and therefore motor lifetime. Considerable fuel savings are achieved through the extremely low viscosity grade SAE 0W-20. **Divinol Syntholight WV 0W-20** is a **hybrid-ready engine oil (H.E.V / P.E.H.V)** and can also be used in vehicles with an automatic start-stop system.

Divinol Syntholight WV 0W-20 can be deployed in the latest types of VW Group engines as following:

- + 3.0/2.0/1.5/1.4/1.2/1.0 TSI/TFSI/MPI
- + 25/30/35/40/45/55 TFSI
- + 3.0 TDI
- + E- hybrid vehicles

### CHARACTERISTICS

SAE Grade	0W-20
Density/15°C / DIN EN ISO 12185	0,83 g/cm <sup>3</sup>
Viscosity/40°C / ASTM D 7042	40 mm <sup>2</sup> /s
Viscosity/100°C / ASTM D 7042	8.2 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270	184

49460

05/2024-49460-15

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



## TECHNICAL DATA SHEET

# Divinol Syntholight WV 0W-20

Synthetic motoroil 0W-20 with VW 508.00/509.00

---

Flash point (Cleveland) / DIN ISO 2592	> 200°C
--	---------

---

Pour point / ASTM D 7346	-48 °C
--------------------------	--------

---

TBN	8.2 mgKOH/g
-----	-------------

### SPECIFICATION

ACEA C5

### MANUFACTURER APPROVAL

VW 508.00/509.00

### DIVINOL RECOMMENDATION

Porsche C20; Ford WSS-M2C956-A1

### APPLICATION

**Divinol Syntholight WV 0W-20** keeps the engine powerfully clean, with significant lower fuel consumption as well as CO<sub>2</sub> emissions. At cold starts, excellent flowability of the oil at low temperatures minimizes wear.

**ATTENTION: Divinol Syntholight WV 0W-20 may not be filled in vehicles requiring VW norm 504.00 / 507.00.**

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49460

05/2024-49460-15

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.