



TECHNICAL DATA SHEET

Divinol Syntholight 5W-40

High performance 5W-40 motor oil

PRODUCT DESCRIPTION

Divinol Syntholight 5W-40 is a smooth running engine oil based on the most modern HC synthesis technology. This product guarantees excellent running properties, low abrasion and measurable fuel savings due to the reduction of friction as well as a good cold starting performance. Divinol Syntholight 5W-40 has a high resistance against oxidation and the well balanced additive system avoids sludge in oil.

CHARACTERISTICS

Colour / DIN ISO 2049	4.0
SAE Grade	5W40
Density/15°C / DIN EN ISO 12185	0,860 g/cm ³
Ash / Sulfate DIN 51575	0.9 %
Viscosity/40°C / ASTM D 7042	87 mm ² /s
Viscosity/100°C / ASTM D 7042	14.3 mm ² /s
Viscosity index / ASTM D 2270	172
Flash point (Cleveland) / DIN ISO 2592	>= 195 °C

49520

02/2024-49520-20

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Syntholight 5W-40

High performance 5W-40 motor oil

Pour point / ASTM D 7346	-39 °C
--------------------------	--------

TBN	10.8 mgKOH/g
-----	--------------

SPECIFICATION

API SP/CF; ACEA A3/B4

MANUFACTURER APPROVAL

MB-Approval 229.3

DIVINOL RECOMMENDATION

Porsche A40; Renault RN 0700/0710; VW 502.00/505.00; GM-LL-A-025; GM-LL-B-025; BMW Longlife-01 (<2019); FIAT 9.55535 N2; PSA B71 2296

APPLICATION

Divinol Syntholight 5W-40 is designed for spark ignition and diesel engines with or without turbo charger.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49520

02/2024-49520-20

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.