



TECHNICAL DATA SHEET

Divinol Super 10W-40

Multigrade Oil SAE 10W40

PRODUCT DESCRIPTION

Multigrade engine oil, which is characterized by an optimal viscosity-temperature behavior and an excellent cleaning as well as mud carrying capacity due to optimal additivation of Divinol Super 10W-40.

CHARACTERISTICS

SAE Grade	10W40
Density/15°C / DIN EN ISO 12185	0,865 g/cm ³
Viscosity/40°C / ASTM D 7042	84 mm ² /s
Viscosity/100°C / ASTM D 7042	12.7 mm ² /s
Viscosity index / ASTM D 2270	149
Flash point (Cleveland) / DIN ISO 2592	>240 °C
Pour point / ASTM D 7346	-33 °C
TBN	9 mgKOH/g

SPECIFICATION

API SL/CF/CF-4; JASO MA

49625

08/2022-49625-10

This information corresponds to our current knowledge. They do not exempt the processor from carrying out its own tests. A legally binding assurance of certain properties or a suitability for a specific application cannot be derived from our information. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the recipient of our products himself. We would also like to point out that the specifications of our product always take precedence over objective quality requirements.



TECHNICAL DATA SHEET

Divinol Super 10W-40

Multigrade Oil SAE 10W40

DIVINOL RECOMMENDATION

ACEA A3-98/B4-98/E2-98; VW 505.00/501.01; MB 228.1; Volvo VDS; MAN 271

APPLICATION

HD multi-grade engine oil for superior performance in gasoline and diesel engines.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49625

08/2022-49625-10

This information corresponds to our current knowledge. They do not exempt the processor from carrying out its own tests. A legally binding assurance of certain properties or a suitability for a specific application cannot be derived from our information. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the recipient of our products himself. We would also like to point out that the specifications of our product always take precedence over objective quality requirements.

2 / 2