



## TECHNICAL DATA SHEET

# Divinol Super Turbo 20W-50

Premium SAE 20W50

### PRODUCT DESCRIPTION

Divinol Super Turbo 20W-50 is a multi-purpose engine oil of high quality for mixed fleet use and every season. The optimal additive formulation ensures excellent engine lubrication during all operating conditions. Can be deployed in motorbikes according standard JASO MA. Also suitable for LPG/CNG motors. According to the manufacturer's instructions!

### CHARACTERISTICS

SAE Grade	20W50
Pour point / ASTM D 7346	-24 °C
Density/15°C / DIN EN ISO 12185	0,87 kg/m <sup>3</sup>
Viscosity/100°C / ASTM D 7042	17 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270	142
Flash point (Cleveland) / DIN ISO 2592	230 °C
TBN	10 mgKOH/g

### SPECIFICATION

API SJ/CH-4; MIL-L-2104-E; JASO MA

### MANUFACTURER APPROVAL

49632

12/2023-49632-17

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

## Divinol Super Turbo 20W-50

Premium SAE 20W50

Meet MAN 3275 specification

Meet Caterpillar ECF-1A specification

### DIVINOL RECOMMENDATION

DTFR 15B110 (MB 228.3); MB 228.1; Allison C-4; Deutz DQC-II; Caterpillar TO-2; Renault RLD; Volvo VDS; MTU Type 2 ; MACK EO-M+; Cummins CES 20077; VW 501.01/ 505.00; ZF-TE ML 03A/07D

### APPLICATION

Multi-purpose motor oil for all otto and diesel engines including turbo-supercharger.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49632

12/2023-49632-17

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

2 / 2