



TECHNICAL DATA SHEET

Divinol Turbo 15W-40

Mineral oil based engine oil SAE 15W-40

PRODUCT DESCRIPTION

Divinol Turbo 15W-40 is a SHPD-multigrade oil, which can be used for the whole motor vehicle fleet. Outstanding cleaning and dirt carrying properties (dispersant and detergent properties) enable longer oil change intervals (according to the manufacturer). The oil simplifies stock keeping in mixed vehicle fleets because of universal, all season usability for diesel and otto engines.

CHARACTERISTICS

SAE Grade	15W40
Density/15°C / DIN EN ISO 12185	0,870 g/cm ³
Viscosity/40°C / ASTM D 7042	119 mm ² /s
Viscosity/100°C / ASTM D 7042	16 mm ² /s
Viscosity index / ASTM D 2270	144
Flash point (Cleveland) / DIN ISO 2592	230°C
Pour point / ASTM D 7346	-33 °C °C
TBN	11 mgKOH/g

SPECIFICATION

API SJ/CF-4

49681

03/2024-49681-10

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Turbo 15W-40

Mineral oil based engine oil SAE 15W-40

DIVINOL RECOMMENDATION

VW 501.01/ 505.00; Allison C-4; Caterpillar TO-2; Volvo VDS; MAN 271; MB 228.1; MB 229.1; MTU Type 1; Valtra E

APPLICATION

For supercharged, fast running diesel / gasoline engines in utility vehicles (busses, transporters, heavy goods vehicles for building work) which are in permanent use with dirt, dust, heat and cold influence.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49681

03/2024-49681-10

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

2 / 2