



TECHNICAL DATA SHEET

Divinol Syntholight C2 5W-30

High-Tech 5W-30 according ACEA C2

PRODUCT DESCRIPTION

Divinol Syntholight C2 5W-30 is a special HC-Synthetic oil for modern diesel and fuel driven motors. The formulation „Fuel Economy“ guarantees fuel saving deployment. This quality product ensures fast oiling of the motor, especially during the start and warm up phase. **Divinol Syntholight C2 5W-30** is well suited for vehicles of French and Asian manufacturers. Additionally **Divinol Syntholight C2 5W-30** can be deployed for LPG/CNG driven motors. Please see manufacturer's technical regulations.

CHARACTERISTICS

Viscosity/40°C / ASTM D 7042	70 mm ² /s
------------------------------	-----------------------

SAE Grade	5W30
-----------	------

Density/15°C / DIN EN ISO 12185	0,85 g/cm ³
---------------------------------	------------------------

Viscosity/40°C / DIN EN ISO 3104	70 mm ² /s
----------------------------------	-----------------------

Viscosity/100°C / ASTM D 7042	12 mm ² /s
-------------------------------	-----------------------

Viscosity index / ASTM D 2270	168
-------------------------------	-----

Flash point (Cleveland) / DIN ISO 2592	>= 180 °C
--	-----------

Pour point / ASTM D 7346	-42 °C
--------------------------	--------

TBN	8.5 mgKOH/g
-----	-------------

SPECIFICATION

49700

03/2024-49700-29

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Syntholight C2 5W-30

High-Tec 5W-30 according ACEA C2

API SN/CF; ACEA C2; ILSAC GF-5

DIVINOL RECOMMENDATION

PSA B71 2288/PSA B71 2290 (<2017), PSA B71 2295, Fiat 9.55535 S1, Iveco 18-1811 SC1, Citroen*, Toyota*, Honda*, Mazda*

*according service manual of OEM

APPLICATION

Divinol Syntholight C2 5W-30 is recommended for Otto- and Diesel engines in Fiat, Toyota, Honda, Mazda with or without exhaust after treatment systems considering the manufacturers instructions in each case.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49700

03/2024-49700-29

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

2 / 2