



## TECHNICAL DATA SHEET

# Divinol Multimax Top 15W-40

## Premium Fleetoil SAE 15W40

### PRODUCT DESCRIPTION

Divinol Multimax Top 15W-40 is specifically designed for heavy duty, high performance diesel engines. The high additive amount guarantees low friction, long engine life and therefore trouble-free engine operation under extreme conditions. Furthermore longer oil drain intervals in diesel engines are possible (depending on manufacturer's instructions). Divinol Multimax Top 15W-40 provides optimum engine cleanliness, even under the most difficult conditions. Note: Do not use in Detroit- or GM-Allison two stroke Diesel engines.

#### Advantages:

- + very good protection against piston deposits
- + effective oxidation resistance
- + low oil consumption due to lower evaporation loss
- + robust oil film under high pressure and temperature

### CHARACTERISTICS

SAE Grade	15W-40
Appearance	brown, clear
Density/15°C / DIN EN ISO 12185	0,873 g/cm <sup>3</sup>
Ash / Sulfate DIN 51575	1.4
Viscosity/40°C / ASTM D 7042	92 mm <sup>2</sup> /s
Viscosity/100°C / ASTM D 7042	13.3 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270	145

49720

08/2023-49720-31

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



## TECHNICAL DATA SHEET

# Divinol Multimax Top 15W-40

Premium Fleetoil SAE 15W40

---

Flash point (Cleveland) / DIN ISO 2592	217 °C
--	--------

---

Pour point / ASTM D 7346	-33°C
--------------------------	-------

---

TBN	10.5 mgKOH/g
-----	--------------

### SPECIFICATION

API CI-4/SL; ACEA E7; Jaso DH-1; Global DHD-1

### MANUFACTURER APPROVAL

DTFR 15B110 (MB-Approval 228.3); Volvo VDS-III; Renault RLD-2; MACK EO-N

Meet Caterpillar MAN M 3275-1 specification

Meet Caterpillar ECF-1A specification

### DIVINOL RECOMMENDATION

John Deere JDQ 78 a; MB 229.1; Deutz DQC III-18; CNH MAT 3507; Cummins CES 20076,20077,20078; Valtra CR; DDC 93215; Komatsu EO15W40DH; MTU Type 2; ZF-TE-ML 04P/07D

### APPLICATION

All-season oil, specifically for mixed vehicle fleets. Common fields of application of Divinol Multimax Top 15W-40 are trucks and vehicles used in agriculture, forestry and construction industry. Also suitable for diesel or gasoline driven passenger cars according to stated ACEA/API level.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49720

08/2023-49720-31

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

## Divinol Multimax Top 15W-40

Premium Fleetoil SAE 15W40

49720

08/2023-49720-31

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

3 / 3

**EXPERTLY DONE.**