



TECHNICAL DATA SHEET

Divinol Multimax Plus 10W-40

High quality low ash motor oil for commercial vehicle SAE 10W40

PRODUCT DESCRIPTION

Divinol Multimax Plus 10W-40 is a MHPD (Maximum High Performance Diesel) diesel engine oil based on HC-synthesis technology with an excellent cold-start performance which prevents engine wear. Especially formulated for modern EURO Level diesel engines with low sulphate ash, phosphor and sulphur content. Designed and adjusted to the hardest service conditions in the field of commercial vehicles equipped with diesel particle filter (DPF) or catalytic converter (SCR) and use of diesel oil with low sulphur content < 50 ppm. Prolonged oil-change intervals are possible if manufacturers instructions are kept. Also suitable for diesel CNG/ LNG motors (not for LPG/CNG) according to the manufacturer's instructions!

CHARACTERISTICS

SAE Grade	10W-40
Colour / DIN ISO 2049	4.5
Appearance	slightly brown, clear
Density/15°C / DIN EN ISO 12185	0,860 g/cm ³
Ash / Sulfate DIN 51575	0.9 %
Viscosity/40°C / ASTM D 7042	92 mm ² /s
Viscosity/100°C / ASTM D 7042	13.7 mm ² /s
Viscosity index / ASTM D 2270	150

49750

12/2023-49750-49

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Multimax Plus 10W-40

High quality low ash motor oil for commercial vehicle SAE 10W40

Flash point (Cleveland) / DIN ISO 2592	245 °C
--	--------

Pour point / ASTM D 7346	-39 °C
--------------------------	--------

TBN	10 mgKOH/g
-----	------------

SPECIFICATION

API CI-4; ACEA E8/E7/E6; JASO DH-2

MANUFACTURER APPROVAL

DTFR15C110; Volvo VDS-4.5; Renault RLD-3; MACK EOS-4.5; Deutz DQC IV-18-LA

Meet MAN 3477; MAN 3271-1 specification

Meet Caterpillar ECF-1A/ ECF 2 specification

DIVINOL RECOMMENDATION

MB 228.51; DTFR 15C100 (MB 228.31); DTFR 13D100 (MB 235.27); MB 226.9; CNH MAT 3521; Scania LDF-LA; DAF HP 2/ LA; Renault Truck RXD, Cummins CES 20076/20077; MTU Type 3.1

APPLICATION

Divinol Multimax Plus 10W-40 is a high-class smooth-running engine oil for application in diesel engines of commercial vehicles with and without supercharging. This product is especially recommended for commercial vehicles e. g. of forwarding agents and municipal car pools. Divinol Multimax Plus 10W-40 must not be used in spark-ignition engines!

49750

12/2023-49750-49

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Multimax Plus 10W-40

High quality low ash motor oil for commercial vehicle SAE 10W40

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49750

12/2023-49750-49

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

3 / 3