



TECHNICAL DATA SHEET

Divinol Multimax Top 20W-50

Premium Fleetoil SAE 20W50

PRODUCT DESCRIPTION

Divinol Multimax Top 20W-50 is specifically designed for heavy duty, high performance diesel engines. Divinol Multimax Top 20W-50 often is used in truck, construction machine and similar sectors. The high additive amount guarantees low friction, long engine life and therefore trouble-free engine operation under extreme conditions. Furthermore longer oil drain intervals in diesel engines are possible (depending on manufacturer's instructions). Divinol Multimax Top 20W-50 provides optimum engine cleanliness, even under the most difficult conditions.

Advantages:

- + very good protection against deposits
- + effective oxidation resistance
- + low oil consumption due to lower evaporation loss
- + good sealing behavior of oil

CHARACTERISTICS

SAE Grade	20W50
Appearance	brown, clear
Density/15°C / DIN EN ISO 12185	0,878 g/cm ³
Ash / Sulfate DIN 51575	1.4 %
Viscosity/40°C / ASTM D 7042	150 mm ² /s
Viscosity/100°C / ASTM D 7042	18.9 mm ² /s

49760

09/2023-49760-10

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Multimax Top 20W-50

Premium Fleetoil SAE 20W50

Viscosity index / ASTM D 2270	144
-------------------------------	-----

Flash point (Cleveland) / DIN ISO 2592	225 °C
--	--------

Pour point / ASTM D 7346	<= 21 °C
--------------------------	----------

SPECIFICATION

API CI-4/SL; Global DHD-1

MANUFACTURER APPROVAL

Meet Caterpillar ECF-1A specification

DIVINOL RECOMMENDATION

ACEA E7/A3/B4; MAN M 3275; DTFR 15B110 (MB 228.3); MB 229.1; Renault RLD-2 ; MTU Type 2; MACK EO-M+; Volvo VDS-III; John Deere JDQ 78 a; Cummins CES 20076,20077, 20078; Valtra CR; Komatsu

APPLICATION

All-season oil, specifically for mixed vehicle fleets. Common fields of application of Divinol Multimax Top 20W-50 are trucks and vehicles used in agriculture, forestry and construction industry. Also suitable for diesel or gasoline driven passenger cars according to stated ACEA/API level.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49760

09/2023-49760-10

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.