



Divinol Multimax Premium FE 5W20

Low HTHS HD oil of the latest generation SAE 5W-20

PRODUCT DESCRIPTION

Divinol Multimax Premium FE 5W20 is a truck engine oil of the latest generation for low SAPS engines. This new, modern oil technology enables a reduced HTHS viscosity and thus fuel savings (compared to HD engine oils with normal HTHS viscosity) as well as optimum wear protection for the engine. The engine oil is resource-saving and economical advantageous resulting in monetary savings as well as reduced exhaust gas emissions. **Divinol Multimax Premium FE 5W20** oil can be used for the latest Euro standard and allows extended oil change intervals.

Advantages:

- + very good protection against oil deposits on pistons
- + low engine wear
- + high oxidation resistance
- + Fuel savings and thus favorable business conditions
- + very good protection of the exhaust aftertreatment systems, the diesel particle filter
- + Offers extended oil change intervals (depending on manufacturer specifications)

CHARACTERISTICS

SAE Grade	5W20
Appearance	brown, clear
Density/15°C / DIN EN ISO 12185	0,85 g/cm ³
Viscosity/100°C / ASTM D 7042	8 mm ² /s
Flash point (Cleveland) / DIN ISO 2592	240 °C

49820

09/2023-49820-2

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Multimax Premium FE 5W20

Low HTHS HD oil of the latest generation SAE 5W-20

Pour point / ASTM D 7346	-42 °C
--------------------------	--------

TBN	10 mgKOH/g
-----	------------

MANUFACTURER APPROVAL

MAN 3977

DIVINOL RECOMMENDATION

Scania LDF-5; DTFR 15C140 (MB 228.71); IVECO 18-1804 Classe TLV LS

APPLICATION

Divinol Multimax Premium FE 5W20 can be used for trucks & HD vehicles that require an engine oil with reduced HTHS. This HD engine oil is recommended for heavy-duty diesel truck engines, including turbochargers and exhaust gas aftertreatment systems, taking into account the respective manufacturer's instructions for extended oil change intervals. This product is not backward compatible with API C classes or ACEA E classes.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49820

09/2023-49820-2

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.