



TECHNICAL DATA SHEET

Divinol Multimax Premium 5W-30

Heavy Duty High-Tech motor oil of latest generation for e.g MAN 3677 and Scania LDF-4

PRODUCT DESCRIPTION

Top modern commercial vehicle motor oil of newest generation for the latest emission regulations. The versatility of Divinol Multimax Premium offers a broad spectrum of use plus the benefit of fuel saving potentials in view of the oils' viscosity grade. The product was developed specifically for low emission LOW SAPS EURO V and EURO VI engines. Thus, this motor oil is used in systems with NOx and/or diesel particulate filters in combination with low sulfur containing diesel (max. 50 ppm). In particular, commercial vehicles deployed with either EGR, SCR and/or diesel particulate filters require an oil quality according to **Divinol Multimax Premium 5W-30**. Additionally the oil can be used in older/different vehicles and offers the possibility of oil stock reduction.

Advantages:

- + very good protection against piston deposits
- + effective oxidation resistance
- + offers significant fuel savings and favorable economic conditions
- + low oil consumption due to lower evaporation loss
- + longer oil drain intervals (depending on the manufacturer's instructions)

CHARACTERISTICS

Colour / DIN ISO 2049	4.5
SAE Grade	5W-30
Density/15°C / DIN EN ISO 12185	0,85 g/cm ³
Ash / Sulfate DIN 51575	0.9 %
Viscosity/40°C / ASTM D 7042	71 mm ² /s

49900

12/2023-49900-8

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Multimax Premium 5W-30

Heavy Duty High-Tech motor oil of latest generation for e.g MAN 3677 and Scania LDF-4

Viscosity/100°C / ASTM D 7042	11.6 mm ² /s
-------------------------------	-------------------------

Viscosity index / ASTM D 2270	160
-------------------------------	-----

Flash point (Cleveland) / DIN ISO 2592	230 °C
--	--------

Pour point / ASTM D 7346	-36 °C
--------------------------	--------

TBN	10 mgKOH/g
-----	------------

SPECIFICATION

ACEA E7/E6

MANUFACTURER APPROVAL

Volvo VDS 3; Renault RLD 2; Mack EO-N; Deutz DQC IV-10 LA

DIVINOL RECOMMENDATION

ACEA E9; DTFR 15C110; MB 228.51; MAN 3677; MAN 3477; Scania LDF 4; DAF HP; Renault RXD; MTU Type 3.1

49900

12/2023-49900-8

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Multimax Premium 5W-30

Heavy Duty High-Tech motor oil of latest generation for e.g MAN 3677 and Scania LDF-4

APPLICATION

Divinol Multimax Premium 5W-30 is recommended for heavy-duty diesel truck, construction, agriculture engines, including turbochargers and catalysts for longest oil drain intervals. Please stick to manufacturer's instructions.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

49900

12/2023-49900-8

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

3 / 3