

TECHNICAL DATA SHEET

# **Divinol Syntholight C2 0W-30**

High-Tec 0W-30 according ACEA C2 formulated on HC base oil & PAO

## **PRODUCT DESCRIPTION**

**Divinol Syntholight C2 0W-30** is a smooth-running engine oil blended with high valuable additives, most advanced HC base oil technology and PAO. The product is recommended for Otto and Diesel engines where an engine oil according ACEA C2 is necessary. A lot of modern cars of PSA Group, Renault, Ford, Fiat, Honda, Mazda, Citroen are designed for `fuel efficiency` which need an oil like **Divinol Syntholight C2 0W-30**. This high-quality engine oil ensures fast lubrication in start and warm-up phases, significantly less engine wear and fuel savings, and thus better emission control. **Divinol Syntholight C2 0W-30** is a hybrid-ready engine oil (H.E.V / P.E.H.V) and can also be used in vehicles with an **automatic start-stop system**.

## **CHARACTERISTICS**

| SAE Grade                              | 0W-30       |
|--|-------------|
| Density/15°C / DIN EN ISO 12185        | 0,840 kg/m³ |
| Viscosity/40°C / ASTM D 7042           | 55 mm²/s    |
| Viscosity/100°C / ASTM D 7042          | 10.9 mm²/s  |
| Viscosity index / ASTM D 2270          | > 170       |
| Flash point (Cleveland) / DIN ISO 2592 | ≥ 215 °C    |
| Pour point / ASTM D 7346               | - 36 °C     |
| TBN                                    | 7 mgKOH/g   |

#### **DIVINOL RECOMMENDATION**

EXPERTLY DONE.

49910

02/2024-49910-16

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

# **Divinol Syntholight C2 0W-30**

High-Tec 0W-30 according ACEA C2 formulated on HC base oil & PAO

ACEA C2; BMW LL-12 FE; PSA B712312; Ford WSS-M2C-950A; Iveco 18-1811 SC1 LV-16; Jaguar Land Rover STJLR.03.5007; Fiat 9.55535-S1; Fiat 9.55535-GS1; Fiat 9.55535-DS1; Renault\*; Honda\*; Mazda\*; Citroen\*; SsangYong\*

\*according service manual of OEM

### APPLICATION

**Divinol Syntholight C2 0W-30** guarantees a rapid oiling of the the engine even under low temperature conditions and offers a sufficiently thick lubricating film at higher temperatures.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

EXPERTLY DONE.

02/2024-49910-16

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.

2/2

Zeller+Gmelin GmbH & Co. KG · Schlossstraße 20 · 73054 Eislingen/Fils · Germany · Postfach 13 65 · 73054 Eislingen/Fils Phone: +49 7161 802-0 · Fax: +49 7161 802-290 · info@zeller-gmelin.de · Geschäftsführer: Dipl.-Ing. (FH) Siegfried Müller Dipl.-Kfm.WalterJerusalem·Dipl.-Ing.(FH)ThomasAlpers·KommanditgesellschaftSitzEislingen·AmtsgerichtUlmHRA530107 Persönlich haftende Gesellschafterin Zeller+Gmelin Verwaltungs GmbH · Sitz Eislingen · Amtsgericht Ulm HRB 530641