



## TECHNICAL DATA SHEET

# Divinol Syntroc TS 10W-40

Modern STOU Tractoroil SAE 10W-40 (also for tractor CVT use)

### PRODUCT DESCRIPTION

Super Tractor Oil Universal (STOU) for use in engines, gearboxes, CVT gears, hydraulic systems and “wet brakes” of agricultural equipment and construction machinery. New types of additives and synthetic base oils guarantee light-running properties and improve cold starting properties.

Advantages:

- + reduces braking noises
- + protects against rust and corrosion
- + reduces stock-keeping and handling costs
- + flows easily even at low temperatures
- + suitable for CVT gears

### CHARACTERISTICS

Colour / DIN ISO 2049	4.5
SAE Grade	10W-40 / SAE 80W-90
Appearance	brown, clear
Density/15°C / DIN EN ISO 12185	871 kg/m <sup>3</sup>
Viscosity/40°C / ASTM D 7042	88.5 mm <sup>2</sup> /s
Viscosity/100°C / ASTM D 7042	13.2 mm <sup>2</sup> /s
Viscosity index / ASTM D 2270	150

51910

03/2024-51910-33

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



## TECHNICAL DATA SHEET

# Divinol Syntnac TS 10W-40

Modern STOU Tractoroil SAE 10W-40 (also for tractor CVT use)

---

Flash point (Cleveland) / DIN ISO 2592 > 210 °C

---

Pour point / ASTM D 7346 < -30 °C

### SPECIFICATION

API GL-4/GL-5 low torque Application; HVLP (DIN 51524 Teil 2/3)

### MANUFACTURER APPROVAL

ZF TE-ML 06B/07B (ZF001626); MF CMS M 1145 (GIMA)\*

\*in work

### DIVINOL RECOMMENDATION

ACEA E7 (E5/E3)/E4; API CI-4; Fendt CVT; CASE MS 1204/1206/1207/1209; CNH MAT 3505/3509/3525; DEUTZ DQC I-02; Deutz DQC II-10 Ford M2C-41B/86B&C/121E/134D/159B&C; Kubota UDT; Fiat AF 87; JCB-Standard 4004/6300; IHC B6; Ford-New Holland 024C, 324B, 410B, 420A, 540B; New Holland NH82009201/2/3; John Deere J20C/J27; MF CMS M 1135/1139/1143/1144; Sunstrand/ Danfoss Hydrostatic Trans Fluid; Sperry Vickers/Eaton M2950S/ I-280-S; MB 228.1; Allison C-4; Caterpillar TO-2; ZF TE-ML 05K /06A/06C/06F/06L/06R/07D

### APPLICATION

Super Tractor Oil Universal (STOU) for universal usage in engines, gears, "wet brakes" and hydraulic systems of agricultural equipment and construction machinery.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

51910

03/2024-51910-33

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.