



TECHNICAL DATA SHEET

Divinol Mischerschutz Spezial

Mixer protection for universal use with high corrosion protection

PRODUCT DESCRIPTION

- + universal mixer protection based on selected mineral oils
- + high corrosion protection
- + ready to use
- + easily sprayable

CHARACTERISTICS

Colour / DIN ISO 2049 lighter 4.5

Density/15°C / DIN EN ISO 12185 890 kg/m³

Viscosity/20°C / ASTM D 7042 21 mm²/s

Flash point (Cleveland) / DIN ISO 2592 > 130 °C

Pour point / ASTM D 7346 -15 °C

Giscode BTM 20

Water hazardous class 1

APPLICATION

Divinol Mischerschutz Spezial is a mixer protection for universal use in concrete mixer trucks, concrete pumps, concrete mixing facilities, construction vehicles etc. It prevents the adhesion of concrete on steel, metal and painted surfaces. The product does not affect rubber and plastic material and it preserves all painted parts. However, preliminary tests are recommended.

91560

02/2024-91560-14

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.



TECHNICAL DATA SHEET

Divinol Mischerschutz Spezial

Mixer protection for universal use with high corrosion protection

Divinol Mischerschutz Spezial should be applied daily before starting up the vehicles and construction machinery

(application by spray gun, compressor, hand sprayer or brush!).

When using **Divinol Mischerschutz Spezial** the quality of the concrete will not be affected - provided that the processing instructions have been followed.

MISCELLANEOUS

Consumption:

Depending on the type of surface and application, approx. 30-50 g/m²

Processing:

The formwork must be pre-cleaned and dry. **Divinol Mischerschutz Spezial** is sprayed evenly and thinly with a high-pressure sprayer at 4-6 bar. Avoid accumulation of release agents. Concrete can be poured immediately after spraying.

Delivery form:

Container 1000 l

Barrels 200 l

Canister 20 l

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

91560

02/2024-91560-14

The information contained in this document (the "Product Specification") is based on our present knowledge. They do not exempt the processor or user from carrying out its own tests. Properties of the product going beyond the above-mentioned specifications and/or suitability for a specific purpose cannot be derived from the product specification and are not owed. Any existing legal provisions and regulations concerning the handling and use of the products must be observed by the processor or user of our products. We expressly point out that the owed quality of our product is measured exclusively on the basis of the properties warranted in this document; the fulfillment of additional legal objective quality requirements is not owed. By ordering our product without objection, being aware of this product specification, you agree to it.