

Revision date:
25.03.2024**MULTIFORM PLAST HIGH LIQUID****Article No.: 20650**

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

20650 MULTIFORM PLAST HIGH LIQUID

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Concrete release agent

1.3. Details of the supplier of the safety data sheet

Company name:	Zeller+Gmelin GmbH & Co. KG	
Street:	Schlossstr. 20	
Place:	D-73054 Eislingen	
Telephone:	+49 (0) 7161 / 802-0	Telefax: +49 (0) 7161 / 802-290
E-mail:	info@zeller-gmelin.de	
Contact person:	Thorsten Grönig	Telephone: +49 (0) 7161 / 802-268
E-mail:	produktsicherheit@zeller-gmelin.de	
Internet:	www.zeller-gmelin.de	
Responsible Department:	Produktsicherheit / Product Safety	

1.4. Emergency telephone number:

In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 - 08454 24 24 24

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

distillates (petroleum), hydrotreated light paraffinic hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30%)

Signal word: Danger**Pictograms:****Hazard statements**

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P102	Keep out of reach of children.
P262	Do not get in eyes, on skin, or on clothing.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No further relevant information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Revision date:
25.03.2024

MULTIFORM PLAST HIGH LIQUID
Article No.: 20650

Page 2 of 8

Chemical characterization

Mineral oil-based mixture. Mineral oil with DMSO extract < 3 % as measured by IP 346.

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-55-8	distillates (petroleum), hydrotreated light paraffinic			25 - < 100 %
	265-158-7	649-468-00-3	01-2119487077-29	
	Asp. Tox. 1; H304			
	hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30%)			25 - < 100 %
	920-360-0		01-2119448343-41	
	Asp. Tox. 1; H304 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
	920-360-0	hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30%)	25 - < 100 %
	inhalation: LC50 = > 5,28 mg/l (dusts or mists); dermal: LD50 = > 2000,0 mg/kg; oral: LD50 = > 4150 mg/kg		

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

When in doubt or if symptoms are observed, get medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures
5.1. Extinguishing media
Suitable extinguishing media

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂).

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO₂). Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Revision date:
25.03.2024

MULTIFORM PLAST HIGH LIQUID
Article No.: 20650

Page 3 of 8

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

SECTION 6: Accidental release measures
6.1. Personal precautions, protective equipment and emergency procedures
General advice

Protective measures: see section 7 + 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

6.3. Methods and material for containment and cleaning up
Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Protective measures: see section 7 + 8.

SECTION 7: Handling and storage
7.1. Precautions for safe handling
Advice on safe handling

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

Advice on protection against fire and explosion

No special measures are necessary.

Advice on general occupational hygiene

When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Protect against: Frost. Keep away from heat. Protect from direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-55-8	distillates (petroleum), hydrotreated light paraffinic			
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m ³
Worker DNEL, long-term		inhalation	local	5,58 mg/m ³

Revision date:
25.03.2024

MULTIFORM PLAST HIGH LIQUID
Article No.: 20650

Page 4 of 8

PNEC values

CAS No	Substance	
	Environmental compartment	Value
64742-55-8	distillates (petroleum), hydrotreated light paraffinic	
	Secondary poisoning	9,33 mg/kg

Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift

Y: A risk of reproductive effects needs not to be feared if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

Z: A risk of reproductive effects cannot to be excluded if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

blood (B)

Urine (U)

8.2. Exposure controls
Appropriate engineering controls

See section 7. No additional measures necessary.

Individual protection measures, such as personal protective equipment
Eye/face protection

Eye glasses with side protection (EN ISO 16321).

Hand protection

Wear suitable gloves. Recommended glove articles: EN ISO 374. Suitable material: NBR (Nitrile rubber).

Breakthrough time: > 480 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Skin protection

Protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. When splashes or fine mist form, a permitted breathing apparatus suitable for these purposes must be used. Suitable respiratory protection apparatus: Filtering Half-face mask (EN 149), e.g. FFA P / FFP3.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	yellowish
Odour:	characteristic

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	not determined
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	6,5 vol. %
Flash point:	140 °C EN ISO 2592
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined

Revision date:
25.03.2024

MULTIFORM PLAST HIGH LIQUID
Article No.: 20650

Page 5 of 8

pH-Value:	not applicable
Viscosity / kinematic: (at 20 °C)	8 mm ² /s ASTM D 7042
Water solubility:	insoluble
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	< 0,1 hPa
Density (at 15 °C):	0,84 g/cm ³ DIN EN ISO 12185
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information
Other safety characteristics

Pour point:	-18 °C ASTM D 7346
Viscosity / dynamic:	not determined
Flow time:	not determined

Further Information

No further relevant information available.

SECTION 10: Stability and reactivity
10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No information available.

SECTION 11: Toxicological information
11.1. Information on hazard classes as defined in GB CLP Regulation
Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30%)				
	oral	LD50 > 4150 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 > 2000,0 mg/kg	Rabbit	ECHA Dossier	
	inhalation (4 h) dust/mist	LC50 > 5,28 mg/l	Rat	ECHA Dossier	

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Revision date:
25.03.2024

MULTIFORM PLAST HIGH LIQUID
Article No.: 20650

Page 6 of 8

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards
Other information

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel.

SECTION 12: Ecological information
12.1. Toxicity

There are no data available on the mixture itself.

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30%)			
	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D	60,7%	28	ECHA Dossier
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
	hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30%)	> 3,50

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

Revision date:
25.03.2024**MULTIFORM PLAST HIGH LIQUID****Article No.: 20650**

Page 7 of 8

Contaminated packaging

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

SECTION 14: Transport information**Land transport (ADR/RID)**

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Marine pollutant: NO

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No data available

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Directive 2010/75/EU on industrial emissions: 0 %

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,4,5,6,7,8,9,10,11,12,13,14,15,16.

Safety Data Sheet

according to UK REACH Regulation

Revision date:
25.03.2024

MULTIFORM PLAST HIGH LIQUID

Article No.: 20650

Page 8 of 8

Abbreviations and acronyms

Asp. Tox: Aspiration hazard
ADR: Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
CAS: Chemical Abstracts Service (a division of the American Chemical Society)
DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
WEL (UK): Workplace Exposure Limits
TWA (EC): Time-Weighted Average
STEL (EC): Short Term Exposure Limit
ATE: Acute Toxicity Estimate
LD50: Lethal Dose, 50% (median lethal dose)
LC50: Lethal Concentration, 50% (median lethal concentration)
EC50: half maximal Effective Concentration
ErC50: EC50 in terms of reduction of growth rate
AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

Safety Data Sheet according to COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)