

according to Regulation (EC) No 1907/2006

Divinol Schalwachs pastös

04.06.2024 Article No.: 81660 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Revision date:

81660 Divinol Schalwachs pastös

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Concrete release agent

1.3. Details of the supplier of the safety data sheet

Company name: Zeller+Gmelin GmbH & Co. KG

Street: Schlossstr. 20
Place: D-73054 Eislingen

Telephone: +49 (0) 7161 / 802-0 Telefax: +49 (0) 7161 / 802-290

E-mail: info@zeller-gmelin.de

Contact person: Thorsten Grönig Telephone: +49 (0) 7161 / 802-268

E-mail: produktsicherheit@zeller-gmelin.de

Internet: www.zeller-gmelin.de

Responsible Department: Produktsicherheit / Product Safety

1.4. Emergency telephone GBK/Infotrac ID 103334 international: (001) 352 323 3500

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226 STOT SE 3; H336 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

hydrocarbons, C8-C9, isoalkanes **Signal word:**Warning

Pictograms:





Hazard statements

H226 Flammable liquid and vapour.H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing mist/vapours/spray.
P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.



according to Regulation (EC) No 1907/2006

Divinol Schalwachs pastös

04.06.2024 Article No.: 81660 Page 2 of 8

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Revision date:

No further relevant information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Hydrocarbon-based mixture.

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
	hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			25 - < 100 %
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412 EUH066			
246538-71-6	hydrocarbons, C8-C9, isoalkanes			10 - < 20 %
	932-020-9		01-2119548395-31	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H304 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
	927-241-2	hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	25 - < 100 %
	inhalation: LC50 = 4951,0 mg/l (vapours); dermal: LD50 = >5000,0 mg/kg; oral: LD50 = >4951,0 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

When in doubt or if symptoms are observed, get medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media



Revision date:

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Divinol Schalwachs pastös

04.06.2024 Article No.: 81660 Page 3 of 8

Suitable extinguishing media

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO2).

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO2). Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Protective measures: see section 7 + 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Protective measures: see section 7 + 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

Advice on protection against fire and explosion

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment. Therefore keep away from fire and sources of ignition. Provide earthing of containers, equipment, pumps and ventilation facilities. Use non-sparking tools. Recommendation: Wear anti-static footwear and clothing

Advice on general occupational hygiene

When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Protect against: Frost. Keep away from heat. Protect from direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

Revision date: Divinol Schalwachs pastös
04.06.2024 Article No.: 81660 Page 4 of 8

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
8002-74-2	Paraffin wax, fume	-	2		TWA (8 h)	
		-	6		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			
Worker DNEL, long-term		dermal	systemic	77 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	871 mg/m³
Consumer DNEL, long-term		dermal	systemic	46 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	185 mg/m³
Consumer DNEL, long-term		oral	systemic	46 mg/kg bw/day
8002-74-2	paraffin waxes and hydrocarbon waxes			
Worker DNEL,	long-term	inhalation	systemic	8,8 mg/m³
Worker DNEL, long-term		dermal	systemic	2,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	2,2 mg/m³
Consumer DNEL, long-term		dermal	systemic	1,25 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	1,25 mg/kg bw/day

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift

Y: A risk of reproductive effects needs not to be feared if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

Z: A risk of reproductive effects cannot to be excluded if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

blood (B)

Urine (U)

8.2. Exposure controls

Appropriate engineering controls

See section 7. No additional measures necessary.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection (EN ISO 16321).

Hand protection

Wear suitable gloves. Recommended glove articles: EN ISO 374. Suitable material: NBR (Nitrile rubber). Breakthrough time: > 120 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Skin protection

Protective clothing.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protection apparatus: Filtering Half-face mask (EN 149), e.g. FFA P / Full-/half-/quarter-face



Revision date:

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Divinol Schalwachs pastös

04.06.2024 Article No.: 81660 Page 5 of 8

masks (EN 136/140) + Combination filtering device, e.g. A P.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Paste Colour: white

Odour: characteristic

Test method

Print date: 19.06.2024

Melting point/freezing point:

Boiling point or initial boiling point and

not determined
not determined

boiling range:

Flammability: Flammable liquid and vapour.
Lower explosion limits: 0,6 vol. %
Upper explosion limits: 7,0 vol. %

Flash point: 37 °C DIN 51755

Auto-ignition temperature:

Decomposition temperature:

pH-Value:

Viscosity / kinematic:

Water solubility:

Partition coefficient n-octanol/water:

Vapour pressure:

not determined
insoluble
not determined
insoluble
not determined

(at 20 °C)

Density (at 20 °C): 0,84 g/cm³ DIN EN ISO 12185

Relative vapour density: not determined Particle characteristics: not applicable

9.2. Other information

Other safety characteristics

Pour point: not determined
Viscosity / dynamic: not determined
Flow time: not determined

Further Information

No further relevant information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008



according to Regulation (EC) No 1907/2006

Revision date: Divinol Schalwachs pastös

04.06.2024 Article No.: 81660 Page 6 of 8

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 >4951,0 mg/kg	Rat		
	dermal	LD50 >5000,0 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 4951,0 mg/l	Rat		

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Other information

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available



Revision date:

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Divinol Schalwachs pastös

04.06.2024 Article No.: 81660 Page 7 of 8

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of Wastes Code - residues/unused products

070604 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease,

soaps, detergents, disinfectants and cosmetics; other organic solvents, washing liquids and mother

liquors; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine pollutant: NO

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No data available

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 40

Directive 2010/75/EU on industrial 60 % (504 g/l)

emissions:

Information according to Directive P5c FLAMMABLE LIQUIDS

2012/18/EU (SEVESO III):

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.



according to Regulation (EC) No 1907/2006

Revision date: Divinol Schalwachs pastös

04.06.2024 Article No.: 81660 Page 8 of 8

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,7,8,9,12,13,14,15,16.

Abbreviations and acronyms

Flam. Liq: Flammable liquid Asp. Tox: Aspiration hazard

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

ADR: Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning

the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations

concerning the International Carriage of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

CAS: Chemical Abstracts Service (a division of the American Chemical Society)

DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average STEL (EC): Short Term Exposure Limit

ATE: Acute Toxicity Estimate

LD50: Lethal Dose, 50% (median lethal dose)

LC50: Lethal Concentration, 50% (median lethal concentration)

EC50: half maximal Effective Concentration ErC50: EC50 in terms of reduction of growth rate

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure		
Flam. Liq. 3; H226	On basis of test data		
STOT SE 3; H336	Calculation method		
Aquatic Chronic 3; H412	Calculation method		

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

Safety Data Sheet according to COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)